

JUN_2020_REV_01

PRE-ASSEMBLED METAL MANIFOLDS FOR UNDERFLOOR HEATING

The pre-assembled Multitubo Manifolds of 1" for underfloor heating and cooling application are made of stainless steel.

The flow manifold includes adjustable flowmeters from 0.1 to 5 l / min, automatic air vent, 1 "ball valve, thermometer from 0°C to 80°C and drain fill valve.

The return manifold includes thermostatic valves, automatic air vent valve, 1 "ball valve, thermometer from 0°C to 80°C and drain fill valve.

The manifold are pre-mounted with isophonic metal brackets and include blanking plug.

The output circuits are compatible with "Euroconus adapters of 3/4" with 50mm spacing.



DIMENSIONS OF THE STAINLESS MANIFOLD:

Ref.	Description	Width (mm)	Height (mm)	Depth. (mm)
4221002	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 2 Cir.	270	320	95
4221003	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 3 Cir.	320	320	95
4221004	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 4 Cir.	370	320	95
4221005	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 5 Cir.	420	320	95
4221006	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 6 Cir.	470	320	95
4221007	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 7 Cir.	520	320	95
4221008	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 8 Cir.	570	320	95
4221009	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 9 Cir.	620	320	95
4221010	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 10 Cir.	670	320	95
4221011	Stainless Steel manifold of 1" – Euroconos outlets 3/4" – 11 Cir.	720	320	95
4221012	Stainless Steel manifold of 1" – Euroconos outlets 3/4"	770	320	95

* The manifolds are supplied pre-assembled in carton boxes. Available from 2 to 12 circuits.